

Reel Packages

To make getting a Hannay reel easier and more convenient, we created specialized reel packages to fit a variety of applications in multiple industries. Based on our most popular models, these packages include the reel, hose, and ball stop for quick, immediate use. And like all Hannay reels, they are engineered of high-quality, durable materials, so you know you can rely on them to provide superior performance for years to come.

N400 Series

Offers a compact hose handling efficiency for twin hose, with 2 inlet swivel joints and 2 outlet risers. Powered by a safe, non-sparking, self-powered spring motor.

OXYGEN/ACETYLENE REELS

Part No.	Description	Size in.	Length ft.	PSI	Ship Wt. lbs.
55-10	N416-19-20-8J* • Twin Grade R hose and HS-35 hose stop installed.	1/4	50	200	103
55-12	N416-19-20-8J* • Twin Grade R hose and HS-35 hose stop installed.	3/8	50	200	109

Notes:

*Specify roller position SR, VR, TR.
 See page 7 of Welding Reels Catalog H-0408-W for specifications and dimensions.
 See page 8 of Hose Reels Catalog H-0308-H for specifications and dimensions.



Torch not included

N500 Series

Offers the same compact frame and narrow base for ease of installation. Plus the advantages of spring rewind for efficient self-powered hose handling in high pressure applications.

GREASE REELS


Part No.	Description	Size in.	Length ft.	PSI	Ship Wt. lbs.
45-11	N515-19-20J H10M* • SAE 100 R2 Type AT hose and HS-35 hose stop installed.	1/4	50	5800	98
45-13	N515-19-20J H8M* • SAE 100 R16 Type AT hose and HS-35 hose stop installed.	3/8	50	4000	99

Notes:

*Specify roller position SR, VR, TR.
 See page 9 of Hose Reel Catalog H-0308-H for specifications and dimensions.



Available Roller Positions*



All Hannay reels are constructed of quality heavy gauge steel (optional aluminum or stainless steel also available on most models).

You Can't Buy A Better Reel.

Reel Packages

N700 Series

Long the industry standard for durable, compact and efficient handling of single hose. Self-powered by industrial duty spring motors.

AIR, WATER, LUBE OIL REELS – LOW PRESSURE

Part No.	Description	Size in.	Length ft.	PSI	Ship Wt. lbs.
47-13	N716-17-18-8L* SHOP AIR ONLY • Single textile braid reinforced synthetic rubber hose and HS-35 hose stop installed.	1/2	50	280	90
47-23	N716-16-17C* • Single textile braid reinforced synthetic rubber hose and HS-35 hose stop installed.	3/8	35	300	90
47-24	N716-19-20J* • Single textile braid reinforced synthetic rubber hose and HS-35 hose stop installed.	1/2	50	280	100
47-29	N716-19-20-10.5J* • Single textile braid reinforced synthetic rubber hose and HS-35 hose stop installed.	3/8	50	300	100

Notes:

*Specify roller position SR, VR, TR.

AIR, WATER, HYDRAULICS, LUBRICATION REELS – MEDIUM PRESSURE

Part No.	Description	Size in.	Length ft.	PSI	Ship Wt. lbs.
47-25	N716-19-20J* SAE 100 R1 Type AT hose and HS-35 hose stop installed.	3/8	50	2600	99
47-26	N716-19-20J* SAE 100 R1 Type AT hose and HS-35 hose stop installed.	1/2	50	2325	102
† 47-46	N716-25-26B* SAE 100 R1 Type AT hose and HS-35 hose stop installed.	1/2	75	2325	150

Notes:

*Specify roller position SR, VR, TR.

†Not able to ship via UPS.

AIR, WATER, HYDRAULICS, LUBRICATION REELS – HIGH PRESSURE

Part No.	Description	Size in.	Length ft.	PSI	Ship Wt. lbs.
47-27	N716-19-20J H4M* SAE 100 R16 Type AT hose and HS-35 hose stop installed.	3/8	50	4000	102
47-28	N716-19-20J H4M* SAE 100 R16 Type AT hose and HS-35 hose stop installed.	1/2	50	3500	105



Notes:

*Specify roller position SR, VR, TR.

See page 12 of Hose Reel Catalog H-0308-H for specifications and dimensions.



Available Roller Positions*



All Hannay reels are constructed of quality heavy gauge steel (optional aluminum or stainless steel also available on most models).

DEF Packages

Diesel Emission Fluid

N800 Series

Long the industry standard for durable, compact, and efficient handling of single hose. Safe, non-sparking, self-powered industrial duty spring motors.

3/4" X 25' DISPENSE REELS

Part No.	Package complete with the following	Ship Wt. lbs.
48-21	N816-19-20-10.5J* <ul style="list-style-type: none"> • 304 stainless steel fluid path • 1" SST peroxide cured swivel joint with EPDM seals • 3/4" female NPT riser • 3/4" x 25' "Tru Blue" DEF hose with 3/4" male NPT fittings • HS-35 hose stop installed 	90



3/4" X 50' DISPENSE REELS

Part No.	Package complete with the following	Ship Wt. lbs.
48-36	N818-23-24-10.5J* <ul style="list-style-type: none"> • 304 stainless steel fluid path • 1" SST peroxide cured swivel joint with EPDM seals • 3/4" female NPT riser • 3/4" x 50' "Tru Blue" DEF hose with 3/4" male NPT fittings • HS-35 hose stop installed 	135



1" X 25' DISPENSE REELS

Part No.	Package complete with the following	Ship Wt. lbs.
48-37	N818-23-24-10.5J* <ul style="list-style-type: none"> • 304 stainless steel fluid path • 1" SST peroxide cured swivel joint with EPDM seals • 1" female NPT riser • 1" x 25' "Tru Blue" DEF hose with 1" male NPT fittings • HS-35 hose stop installed 	134




1" X 50' DISPENSE REELS

Part No.	Package complete with the following	Ship Wt. lbs.
48-42	N818-25-26-10.5B* <ul style="list-style-type: none"> • 304 stainless steel fluid path • 1" SST peroxide cured swivel joint with EPDM seals • 1" female NPT riser • 1" x 50' "Tru Blue" DEF hose with 1" male NPT fittings • HS-35 hose stop installed 	160



Available Roller Positions*



Notes:

*Specify roller position SR, VR, TR.



All Hannay reels are constructed of quality heavy gauge steel (optional aluminum or stainless steel also available on most models).

Fuel Packages

Long-lasting, narrow frame reel with heavy-duty, safe, non-sparking, self-powered spring motor. Designed and built with components for diesel or gasoline fuels.

3/4" X 50' REELS

Part No.	Package complete with the following	Ship Wt. lbs.
48-51	N818-23-24-10.5J* <ul style="list-style-type: none"> • 1" 90° BP Super Swivel with Viton, 1" female NPT riser • 3/4" x 50' Goodyear BC fuel hose (200 psi) • HS-35 hose stop installed 	140

1" X 50' REELS

Part No.	Package complete with the following	Ship Wt. lbs.
48-56	N818-25-26-10.5B* <ul style="list-style-type: none"> • 1" 90° BP Super Swivel with Viton, 1" female NPT riser • 1" x 50' Goodyear BC fuel hose (200 psi) • HS-35 hose stop installed 	164

Notes:

*Specify roller position SR, VR, TR.

Available Roller Positions*



SR (STD)



VR (OPT)



TR (OPT)



TR (Wallmount)



Transport and Delivery

No matter what your application, Hannay diesel emission fluid reel packages will fit your needs.



Bulk – Bulk delivery and transport for 1-1/4" and 1-1/2" hose



Portable – Onsite metered distribution

