**PAGE 1451** JULY 2012

ABCDE

# **Self Priming Centrifugal Pump**



## Models 83A3-B and 83A52-B

Size 3" x 3"

#### **PUMP SPECIFICATIONS**

Size: 3" x 3" (76 mm x 76 mm) NPT - Female.

Casing: Gray Iron 30.

Maximum Operating Pressure 87 psi (600 kPa)\*. Semi-Open Type, Four Vane Impeller: Gray Iron 30. Handles 3/4" (19,1 mm) Diameter Spherical Solids

Impeller Shaft: Carbon Steel 1045.

Replaceable Wear Plate: Carbon Steel 1026.

Pedestal: Gray Iron 30.

Shaft Sleeve: Stainless Steel 304.

Seal Plate: Gray Iron 30.

Flap Valve: Buna-N w/Nylon Reinforcement and Gray Iron 30.

Radial and Thrust Bearings: Open Single Row Ball. Bearing Lubrication: SAE 30 Non-Detergent Oil.

Suction Flange: Gray Iron 25.

Gaskets: Cork.


Hardware: Standard Plated Steel. Discharge Service Tee: Gray Iron 30.

Oil Level Sight Gauge.


Optional Equipment: Strainer.

Consult Factory for Additional Options.


\*Consult Factory for Applications Exceeding Maximum Pressure and/or Temperature Indicated.



83A3-B SEAL DETAIL Type 2, Self-Lubricated. Mechanical. Carbon Rotating Face. Ceramic Stationary Face. Buna-N Elastomers. Stainless Steel 18-8 Cage and Spring. Maximum Temperature of Liquid Pumped, 160°F (71°C).\*



83A52-B SEAL DETAIL Type 31, Mechanical, Self-Lubricated. Silicon Carbide Rotating and Stationary Faces. Fluorocarbon Elastomers (DuPont Viton® or Equivalent). Stainless Steel 18-8 Cage and Spring. Maximum Temperature of Liquid Pumped 160°F (71°C).\*



83A3-B SHOWN



#### THE GORMAN-RUPP COMPANY ● MANSFIELD. OHIO

GORMAN-RUPP OF CANADA LIMITED ● ST. THOMAS, ONTARIO, CANADA

www.grpumps.com


Specifications Subject to Change Without Notice


#### **Specification Data**

SECTION 50, PAGE 1451

APPROXIMATE DIMENSIONS and WEIGHTS

NET WEIGHT: 115 LBS. (52,2 KG.) SHIPPING WEIGHT: 125 LBS. (56,7 KG.) EXPORT CRATE: 8.5 CU. FT. (0,24 CU. M.)







### THE GORMAN-RUPP COMPANY • MANSFIELD, OHIO

GORMAN-RUPP OF CANADA LIMITED ● ST. THOMAS, ONTARIO, CANADA


Specifications Subject to Change Without Notice

Sec. 50


PAGE 1451.1

**JULY 2012** 

ABCDE



**60 HERTZ PERFORMANCE BASED ON** WATER



**BASED ON PETROLEUM** 



THE GORMAN-RUPP COMPANY ● MANSFIELD. OHIO

GORMAN-RUPP OF CANADA LIMITED ● ST. THOMAS, ONTARIO, CANADA

Specifications Subject to Change Without Notice

**Curve Data** 

Sec. 50


**PAGE 1451.2** 

**JULY 2012** 

ABCDE

PERFORMANCE FOR 50 HERTZ TOTAL HEAD PERFORMANCE CURVE **APPLICATIONS** PSI FT 6882-A VOLUTE .

**50 HERTZ PERFORMANCE BASED ON WATER** 





THE GORMAN-RUPP COMPANY ● MANSFIELD, OHIO

GORMAN-RUPP OF CANADA LIMITED • ST. THOMAS, ONTARIO, CANADA

Specifications Subject to Change Without Notice