

WHY GPI?

**CALL GPI'S TOLL-FREE
CUSTOMER SUPPORT
HOTLINE AND YOU'LL
SPEAK TO A REAL PERSON.**

your GPI Chemical Pump. Typical applications include agriculture, hobby farm and landscape or lawn and garden services. Chemical compatibility is critical when choosing the best pump for the job.



PUMP SPECS



MODEL	PA-120H	PA-200H
PART NUMBER	118003-1 (includes 2-in. union ring) 118602-11 (comes as a Tote-a-Pump assembly)	118003-2 (includes 2-in. union ring) 118602-12 (comes as a Tote-a-Pump assembly)
VOLTAGE & TYPE	115-volt AC - Molded Plastic Housing - Gear	115-volt AC - Molded Plastic Housing - Gear
FLOWRATE	Up to 12 GPM (45 LPM)	Up to 8 GPM (30 LPM)
DUTY CYCLE	30 min. On / 30 min. Off (Cycle will vary with viscosity and temperature)	30 min. On / 30 min. Off (Cycle will vary with viscosity and temperature)
POWER CORD	Three-prong power connector pigtail	Three-prong power connector pigtail
NOZZLE	Order separately (kit available)	Order separately (kit available)
INLET/OUTLET SIZE	1 in. / 1 in.	1 in. / 1 in.
SUCTION PIPE	Order separately (kit available)	Order separately (kit available)
HOSE	Order separately (kit available)	Order separately (kit available)
MOTOR PROTECTION	Automatic thermal protector & circuit breaker	Automatic thermal protector & circuit breaker
UNIQUE FEATURE	Built-in handle with convenient spin collar for easy installation.	The pump of choice for thicker chemicals.
USE WITH	Thin Chemicals (0 to 10 centipoise viscosity) Do not use with gasoline, diesel fuel or micro-encapsulated chemicals.	Medium / Thick Chemicals (10 to 450 centipoise viscosity) Do not use with gasoline, diesel fuel or micro-encapsulated chemicals.
APPROVALS	CSA Certified	CSA Certified
WARRANTY	2 Year	2 Year