



56

Part No.	Size	Press	Vac	Wt.lbs
0056-01-0800	8"	4oz	0.4oz	38
0056-01-0810	8"	8oz	0.4oz	38
0056-01-0820	8"	12oz	0.4oz	38
0056-01-0830	8"	16oz	0.4oz	38

Features

Long Pan, dual combination thief hatch. Ideal for oilfield tanks as base contains spills after sampling. Unit is lockable, with a spring loaded aluminum cover and cast iron base. Standard gasket material is Buna-N with other gasket material available. Settings of 4oz pressure and 0.4oz vacuum are standard. Flange bolt pattern conforms to API pattern.

Bolt Pattern:

(16) - 1/2" dia holes on a 10 3/8" B.C.



256

Part No.	Size	Press	Vac	Wt.lbs
0256-01-0800	8"	4oz	0.4oz	38
0256-01-0810	8"	8oz	0.4oz	38
0256-01-0820	8"	12oz	0.4oz	38
0256-01-0830	8"	1Lb.	0.4oz	38

Features

"Ducks Nest" design of thief hatch with the same internal pressure and vacuum ports as the #56 above.

Bolt Pattern:

(16) - 1/2" dia holes on a 10 3/8" B.C.

Repair Parts Listing

Part Number	Description	Material
0056-01-0803	4 oz Press / 0.4oz Vac Internal Valve Assy	Aluminum
0056-01-0805	4 oz Press / 0.4oz Vac Cover Assembly	Aluminum
0056-03-0806	Handle & Latch Assembly	Aluminum
0056-05-3000	Pressure Gasket	EPDM
0056-05-3001	Vacuum Gasket	EPDM
0056-05-3002	Pressure Gasket	Viton
0056-05-3003	Vacuum Gasket	Viton
0056-05-3004	Pressure Gasket	ECH
0056-05-3005	Vacuum Gasket	ECH
0056-05-3006	Pressure Gasket	Buna-N
0056-05-3007	Vacuum Gasket	Buna-N
0056-05-3050	Envelope Pressure Gasket	Buna-N
0056-17-1808	Hinge Pin	Mild Steel

Maintenance Note:

Check gaskets periodically for cracking or UV damage, replace if necessary. Inspect internal valve for blockage or debris.

Airflow Rating:

56 & 256 Pressure:

549,117 SCFH @ 2.5psig

56 & 256 Vacuum:

13,192 SCFH @ 3"H₂O (-1oz)



Clay and Bailey Mfg. Co.