Model 285 Ductile Iron Line Strainers

SPECIFICATION SHEET

Bottom clean-out Y-type line strainers are used in horizontal pipelines to filter debris and protect downstream equipment.

Features

- 50 PSI operating pressure (except the 4" 285FDI which is 125 PSI)
- · Strainer basket is easily removable for cleaning or replacement
- · NPT female threaded connection

Construction Details

- · Ductile iron body and cap
- 2" and 3" have malleable iron yoke
- · 304 stainless steel screen
- 285FDI 4" size has bolt on cover, no yoke



I.D. Number	Α	В	С	D	E	Length	Height	Weight (lbs)
				6 Mesl	h			
285DI-3000 AS	2"	DI	TF	Т		10"	7.31"	15.0
285DI-3200 AS	3"	DI	TF	Т		12.38"	9.63"	27.50
285FDI1500 AS	3"	DI	TF	F	4	13.75"	10.19"	41.0
285FDI1600 AS	4"	DI	TF	F	8	16"	16.88"	93.0
				10 Mes	h	,	,	
285DI-3400 AS	2"	DI	TF	Т		10"	7.31"	15.0
285DI-3600 AS	3"	DI	TF	Т		12.38"	9.63"	27.5.0
285FDI1700 AS	3"	DI	TF	F	4	13.75"	10.19"	41.0
285FDI1800 AS	4"	DI	TF	F	8	16"	16.88"	93.0
				20 Mes	sh	,	,	
285DI-3800 AS	2"	DI	TF	Т		10"	7.31"	15.0
285DI-4000 AS	3"	DI	TF	Т		12.38"	9.63"	27.50
285FDI1900 AS	3"	DI	TF	F	4	13.75"	10.19"	41.0
285FDI2000 AS	4"	DI	TF	F	8	16"	16.88"	93.0
				40 Mes	h			
285DI-4200 AS	2"	DI	TF	Т		10"	7.31"	15.0
285DI-4400 AS	3"	DI	TF	Т		12.38"	9.63"	27.50
285FDI2100 AS	3"	DI	TF	F	4	13.75"	10.19"	41.0
285FDI2200 AS	4"	DI	TF	F	8	16"	16.88"	93.0
				60 Mes	sh		`	
285DI-4600 AS	2"	DI	TF	Т		10"	7.31"	15.0
285DI-4800 AS	3"	DI	TF	Т		12.38"	9.63"	27.50
285FDI2300 AS	3"	DI	TF	F	4	13.75"	10.19"	41.0
285FDI2400 AS	4"	DI	TF	F	8	16"	16.88"	93.0
				80 Mes	sh			
285DI-5000 AS	2"	DI	TF	Т		10"	7.31"	15.0
285DI-5200 AS	3"	DI	TF	Т		12.38"	9.63"	27.50
285FDI2500 AS	3"	DI	TF	F	4	13.75"	10.19"	41.0
285FDI2600 AS	4"	DI	TF	F	8	16"	16.88"	93.0
				100 Me	sh			
285DI-5400 AS	2"	DI	TF	Т		10"	7.31"	15.0
285DI-5600 AS	3"	DI	TF	Т		12.38"	9.63"	27.50
285FDI2700 AS	3"	DI	TF	F	4	13.75"	10.19"	41.0
285FDI2800 AS	4"	DI	TF	F	8	16"	16.88"	93.0

SPECIFICATION OPTIONS:

A-Size: 2", 3", or 4"

B—Body and cap material: Ductile iron (DI)

C—Gasket: Teflon® (TF)
D—Flanged (F); Threaded (T)
E—Number of bolt holes

Length—Dimension across strainer face to face

Height—Dimension from base to top **Weight—**Shipping weight (lbs)

Flange gaskets, nuts, bolts and washers available.

MORRISON BROS. CO.

570 E. 7th Street, P.O. Box 238 | Dubuque, IA 52004-0238 t. 563.583.5701 | 800.553.4840 | f. 563.583.5028