



# Model 517 Series 3½ Gallon AST Spill Container

SPECIFICATION SHEET

Tank top spill containers are designed to contain small spills that occur at the fill point on aboveground storage tanks.

## Features

- 3½ gallon (13.25 liters) capacity
- Hinged cover is lockable with a padlock
- Centered connection
- **517** has male threaded inlet and outlet
- **517F** has female threaded inlet and outlet
- **517WO** includes removable screen for use as used oil collection point, male threads



## Construction Details

- 16 gauge spun steel, powder coated white body and cover

## Certifications & Listings

- Florida DEP EQ 345
- Meets the new and revised requirements for CAN-ULC-S663-11 (effective September 25, 2015)

| I.D. Number     | A   | B | C | D   | E | F | G      | H      | I     | J      |
|-----------------|-----|---|---|-----|---|---|--------|--------|-------|--------|
| 517---0100 AC   | 3.5 | M | C | 2"  | N | N | 8.13"  | 17.25" | 9.0   | 13.14" |
| 517---0200 AC   | 3.5 | M | C | 4"  | N | N | 8.63"  | 17.25" | 9.0   | 13.14" |
| 517---2500 ACPW | 3.5 | M | C | 2½" | N | N | 8.4"   | 17.25" | 9.0   | 13.14" |
| 517F--0100 AC   | 3.5 | F | C | 2"  | N | N | 8.0"   | 17.25" | 10.50 | 13.14" |
| 517F--0200 AC   | 3.5 | F | C | 4"  | N | N | 10.13" | 17.25" | 10.50 | 13.14" |
| 517F--2500 ACPW | 3.5 | F | C | 2½" | N | N | 8.4"   | 17.25" | 10.50 | 13.14" |
| 517WO-0100 AC   | 3.5 | M | C | 2"  | N | Y | 8.13"  | 17.25" | 11.0  | 13.14" |
| 517WO-0200 AC   | 3.5 | M | C | 4"  | N | Y | 8.64"  | 17.25" | 11.0  | 13.14" |

### SPECIFICATION OPTIONS:

- A—Capacity: Gallons
- B—Mounting Connection: Male (M), Female (F)
- C—Mounting Location: Center (C)
- D—Size: NPT threads
- E—Drain: Yes/No
- F—Screen: Yes/No
- G—Height: (inches)
- H—Width: (inches)
- I—Shipping weight: (lbs)
- J—Body diameter

570 E. 7th Street, P.O. Box 238 | Dubuque, IA 52004-0238

t. 563.583.5701 | 800.553.4840 | f. 563.583.5028

www.morbros.com



MORRISON BROS. CO.