




## OPW 66SB Swivel Breakaway

The OPW 66SB Swivel Breakaway is intended for easy installation at the nozzle inlet. The compact, lightweight design incorporates a 360° swivel rotation at both the male end and middle joint, with a simple and easily-reconnectable breakaway on the opposite end.



### Materials

- Body:** Aluminum
- Sleeve:** Nylon, HDPE
- Seals:** Viton®
- Spring:** Stainless steel
- Poppet:** Aluminum




### Features

- ◆ **UL and ULC listed** for use in gasoline, diesel and up to 10% ethanol blends. Specific listings available at [www.opwglobal.com](http://www.opwglobal.com).
- ◆ **Pull Force** – the 66SB will break away with a pull force of no more than 350 lbs.
- ◆ **Easily Reconnected at Waist Height** – after relieving line pressure, simply push coupling halves together until latched. Reconnection force is approximately 15 lbs.
- ◆ **Protected Coupling and Poppet** – the breakaway’s poppet and sealing surface are protected from impact during separation by a plastic sleeve.
- ◆ **Reduces Connections** – the single-unit design replaces the standard swivel, breakaway and whip hose, eliminating possible leak points.
- ◆ **Double O-Ring Seal** – both swivel joints are protected by a double O-Ring design.

#### Design working pressure

- ◆ 50 psi (3.45 bar) maximum pressure.



### Ordering Specifications

Product #	Size	Weight	
		lbs.	kg
66SB-7575	3/4" x 3/4" (NPT)	1	0.45
66SB-1010	1" x 1" (NPT)	1.82	0.83

### Dimensions

Product #	A		B	
	in.	mm	in.	mm
66SB-7575	2 1/2"	64	5 29/32"	150
66SB-1010	3 1/32"	85	8 1/2"	216

66SB Instruction Sheet Order Number: **F-69**