



Model 939 Fusible Globe/Gate Valve

SPECIFICATION SHEET

Fusible globe/gate valve are used to shut off product flow in the event of fire.

Features

- Fusible element integrated into the hand-wheel melts at 165°F causing the valve to close
- Recommended use with fuel oil and kerosene service
- 10 PSI maximum operating pressure ¼" to ¾" sizes
- 25 PSI maximum operating pressure 1" size
- Not intended for use as a block valve, intended as a normally open valve
- ¼", ⅜", and ½" are UL and ULC listed

Construction Details

- Brass body, bonnet, and stem

WARNING: 939 Series valves require periodic inspection to ensure the shut-off mechanism is operating. Should not be opened under pressure.

| Item Number | Size | Weight (lbs) |
|---------------|------|--------------|
| 939---0050 1V | ¼" | 0.50 |
| 939---0100 1V | ⅜" | 0.50 |
| 939---0200 1V | ½" | 0.75 |
| 939---0300 1V | ¾" | 1.0 |
| 939---0400 1V | 1" | 2.25 |



939 (¼")



MORRISON BROS. CO.

570 E. 7th Street, P.O. Box 238 | Dubuque, IA 52004-0238
t. 563.583.5701 | 800.553.4840 | f. 563.583.5028

www.morbros.com