

# GPI's *NEW MR 5-30* MECHANICAL METER

**2X LONGER LIFE THAN  
THE INDUSTRY'S NEXT  
BEST PERFORMER.**

**NEW**

**GPI**

**METER  
SPECS**



Twist knob makes resetting a snap!

Easy-to-read four digit display

Rotate cover for desired flow direction



Easy access port to field calibrate



Rotate for desired mounting (fittings included)

MODEL	MR 5-30	MR 5-30N
PART NUMBER	126300-01 (3/4 in. NPT, gallons) 126300-03 (1 in. NPT, gallons) 126300-05 (1-1/2 in. NPT, gallons) 126300-02 (3/4 in. NPT, litres) 126300-04 (1 in. NPT, litres) 126300-06 (1-1/2 in. NPT, litres) 126300-07 (3/4 in. BSPP, litres) 126300-08 (1 in. BSPP, litres) 126300-09 (1-1/2 in. BSPP, litres)	126300-23 (1 in. NPT, gallons) 126300-25 (1-1/2 in. NPT, gallons)
CONSTRUCTION & TYPE	Aluminum - Mechanical Nutating Disc	Aluminum - Mechanical Nutating Disc
GALLON & LITRE MODELS	Order gallon or litre model.	Order gallon or litre model.
FLOW RANGE	5-30 GPM (19-114 LPM)	5-30 GPM (19-114 LPM)
ACCURACY	+/- 2% of reading	+/- 2% of reading
PRESSURE RATING	50 PSI (3.4 bar)	50 PSI (3.4 bar)
FIELD CALIBRATION	Yes	Yes
INLET/OUTLET SIZES	3/4 in., 1 in. or 1-1/2 in. NPT or BSPP available	3/4 in. or 1-1/2 in. NPT
DISPLAY	Max. Batch total is 4-digits Cumulative total is 8-digits	Max. Batch total is 4-digits Cumulative total is 8-digits
UNIQUE FEATURE	Large, easy-to-read display with twist knob reset.	Housing is nickle plated with Fluorocarbon seals and stainless steel hardware.
USE WITH	Gasoline, Gasoline/Ethanol blends at levels designated as "gasohol" (E10 maximum), diesel and kerosene.	
APPROVALS	U.L. Listed on NPT models.	U.L. Listed on NPT models.
WARRANTY	2 Year	2 Year