



CONTACT FACTORY FOR M-150S/FM-530 PUMP & METER COMBO UNITS.

pump family to meet your needs from 8 GPM to 25 GPM models. When fuel transfer time is more critical, move up to the 25 GPM pumps found in this section.

 PUMP SPECS	 		
	MODEL	M-150S-B100-MU or -AU	M-180S-ML or -AU
PART NUMBER	110000-126 w/manual nozzle 110000-127 w/auto nozzle	110300-1 w/manual nozzle 110300-2 w/auto nozzle 110300-3 w/manual nozzle & CE Approval 110300-4 w/auto nozzle & CE Approval	110000-70 w/manual nozzle 110000-91 w/manual nozzle & CE Approval
VOLTAGE & TYPE	12-Volt DC - Gear Explosion proof motor.	12-Volt DC - Gear Explosion proof motor.	12-Volt DC - Gear Explosion proof motor.
FLOWRATE	Up to 15 GPM (57 LPM)	Up to 18 GPM (69 LPM)	Up to 15 GPM (57 LPM)
DUTY CYCLE	30 min. On / 30 min. Off	30 min. On / 30 min. Off	30 min. On / 30 min. Off
POWER CORD	18 ft. (5.5m) x 12/2 AWG	18 ft. (5.5m) x 12/2 AWG	18 ft. (5.5m) x 12/2 AWG
NOZZLE	Choice of Manual or Automatic Shutoff	Choice of Manual or Automatic Shutoff	Manual Shutoff
SUCTION PIPE	Adjustable to 40 in.	Adjustable to 40 in.	Adjustable to 40 in.
HOSE	12 ft. (3.7m) x 3/4 in.	12 ft. (3.7m) x 1 in.	12 ft. (3.7m) x 3/4 in.
MOTOR PROTECTION	Circuit breaker for long life.	Circuit breaker for long life.	Circuit breaker for long life.
UNIQUE FEATURE	Convenient Spin Collar for easy installation.	Improved flowrate and convenient Spin Collar.	Convenient Spin Collar for easy installation.
USE WITH	Gasoline (alcohol blends E15), diesel fuel (biodiesel blends B100) and Kerosene.	Gasoline (alcohol blends E15), diesel fuel (biodiesel blends B20) and kerosene.	
APPROVALS	U.L. Listed Motor. CSA Certified Flammable Liquid Dispenser.	U.L. Listed Motor. CSA Certified Flammable Liquid Dispenser.	U.L. Listed Motor. CSA Certified Flammable Liquid Dispenser.
WARRANTY	2 Year	2 Year	2 Year