





WHY GPI?

GPI SERVES A VARIETY OF MARKET NEEDS WORLDWIDE.

Consider one of these models for construction, fleet or large farming applications. You can save time and money using one of these pumps to refuel. These high-flow pumps lead the industry in reliability and durability.

			
MODEL	M-3120-B100-ML or -AL	M-3260-ML or -AL	M-3295-ML or -AL
PART NUMBER	133200-05 w/manual nozzle 133200-06 w/auto nozzle	133210-01 w/manual nozzle 133210-02 w/auto nozzle	133230-01 w/manual nozzle 133230-02 w/auto nozzle
VOLTAGE & TYPE	115-volt AC - Vane	230-volt AC - Vane	230-volt AC - Vane
FLOWRATE	Up to 20 GPM (75 LPM)	Up to 64 LPM @ 50 Hz 76 LPM @ 60 Hz	Up to 95 LPM @ 50 Hz 113.5 LPM @ 60 Hz
DUTY CYCLE	30 min. On / 30 min. Off	30 min. On / 30 min. Off	30 min. On / 30 min. Off
POWER CORD	None	None	None
NOZZLE	Choice of Manual or Automatic Shutoff	Choice of Manual or Automatic Shutoff	Choice of Manual or Automatic Shutoff
INLET/OUTLET SIZE	1 in. / 1 in. (3/4 in. bushing supplied)	1 in. BSPP / 1 in. BSPP (3/4 in. bushing supplied)	1-1/4 in. BSPP / 1 in. BSPP
SUCTION PIPE	None	None	None
HOSE	12 ft. (3.7m) x 3/4 in.	12 ft. (3.7m) x 1 in.	12 ft. (3.7m) x 1 in.
MOTOR PROTECTION	Internal temperature-limiting device.	Internal temperature-limiting device.	Internal temperature-limiting device.
UNIQUE FEATURE	 B100 Fuel requires a minimum operating temperature of 40° F.	Inlet/outlet connections are BSPP threads. Pump bung is 2 in. male BSPT.	Inlet/outlet connections are BSPP threads. Pump bung is 2 in. male BSPT.
USE WITH	Gasoline (up to 15% alcohol blends such as E15), diesel fuel (up to 20% biodiesel blends such as B20), biodiesel (B100) and kerosene.	Diesel fuel.	Diesel fuel.
APPROVALS	U.L. Listed Motor to U.S. and Canadian Standards.	U.L. Listed Motor to U.S. and Canadian Standards. CE	U.L. Listed Motor to U.S. and Canadian Standards. CE
WARRANTY	2 Year	2 Year	2 Year