




# WHY GPI?

**OUR PRODUCT LINE  
INCLUDES METERS FOR  
FUEL, OIL AND WATER.**

GPI Customer Service can recommend the right product for your needs.

 <b>METER SPECS</b>		
<b>MODEL</b>	<b>LM-200</b>	<b>LM-300</b>
<b>PART NUMBER</b>	111316-01 (1 in. NPT inlet/outlet) 111316-04 (3/4 in. NPT inlet/outlet)	120000-28 (1 in. NPT inlet/outlet) Bushings included.
<b>CONSTRUCTION &amp; TYPE</b>	Aluminum - Mechanical, Nutating Disc	PBT Polyester - Nutating Disc
<b>FLOWRATE TYPE</b>	Quarts	Gallons, Quarts, Litres & Ounces
<b>FLOW RANGE</b>	16-80 QPM (15-76 LPM)	8-80 QPM (7.5-76 LPM)
<b>POWERED BY</b>	N/A	One alkaline 9 Volt battery (Average 3-Year use) †
<b>ACCURACY</b>	+/- 2% of reading	+/- 2% of reading
<b>PRESSURE RATING</b>	50 PSI	50 PSI
<b>FIELD CALIBRATION</b>	Yes	Yes
<b>INLET/OUTLET SIZES</b>	LM-200-Q8N 1 in. NPT LM-200-Q6N 3/4 in. NPT	1 in. NPT (3/4 in. bushing included)
<b>DISPLAY</b>	4-digit Display	6-digit Display
<b>UNIQUE FEATURE</b>	Internal strainer helps reduce maintenance.	Two calibration curves set at factory with a third field calibration curve available.
<b>USE WITH</b>	Hydraulic fluid and up to 30W oil. <b>Do not use with flammable fluids.</b>	Motor oil, gear oil, hydraulic oil, antifreeze, ATF and waste oil. <b>Do not use with flammable fluids or antifreeze that exceeds 50% water.</b>
<b>APPROVALS</b>	None	None
<b>WARRANTY</b>	1 Year	1 Year