

12-VOLT PUMPS

CHOOSING A GPI ELECTRIC GEAR PUMP

When it comes to choosing an Electric Pump, GPI makes it easy! At Great Plains Industries, we recognize the differences in the needs of our customers.



MODEL	EZ-8	M-150S-EM
PART NUMBER	137100-01	110000-107
VOLTAGE & TYPE	12-volt DC - Rotary Gear Explosion proof motor.	12-volt DC - Rotary Gear Explosion proof motor.
FLOWRATE	Up to 8 GPM (30 LPM)	Up to 15 GPM (57 LPM)
DUTY CYCLE	15 min. On / 30 min. Off	30 min. On / 30 min. Off
POWER CORD	15 ft. (4.6m) x 14/2 AWG	18 ft. (5.5m) x 12/2 AWG
NOZZLE	Manual Shutoff	Manual Shutoff
INLET/OUTLET SIZE	3/4 in. / 3/4 in.	1 in. / 3/4 in.
SUCTION PIPE	Three-piece, Trim-to-fit	Two-piece, Trim-to-fit
HOSE	10 ft. (3.0m) x 5/8 in.	10 ft. (3.0m) x 3/4 in.
MOTOR PROTECTION	Thermal Protector	Circuit breaker
UNIQUE FEATURE	Gas station equivalent flowrate - direct tank mounting.	Economy model with direct tank mounting.
USE WITH	Gasoline (up to 15% alcohol blends such as E15), diesel fuel (up to 20% biodiesel blends such as B20) and kerosene.	
APPROVALS	Motor is U.L. Listed to U.S. and Canadian Standards	U.L. Listed Motor. CSA Certified Flammable Liquid Dispenser.
WARRANTY	2 Year	2 Year