

12- and 24-VOLT PUMPS

GPI HIGH-FLOW ELECTRIC VANE PUMPS

Special applications require a special pump. Do you need a high-flow 25 GPM pump to transfer fuel in a hurry? GPI offers models with or without hose and nozzle and with



**PUMP
SPECS**



MODEL	M-3025-ML or -AD	M-3025CS-PO	M-3025CB-ML or -AD
PART NUMBER	133240-1 w/manual nozzle 133240-2 w/auto nozzle	133262-03 (Pump only model)	133265-03 w/manual nozzle 133265-04 w/auto nozzle
VOLTAGE & TYPE	12-volt DC - Vane	12-volt DC - Vane	12-volt DC - Vane
FLOWRATE	Up to 25 GPM (95 LPM)	Up to 25 GPM (95 LPM)	Up to 25 GPM (95 LPM)
DUTY CYCLE	30 min. On / 30 min. Off	30 min. On / 30 min. Off	30 min. On / 30 min. Off
POWER CORD	15 ft. (4.6m) of 10/3 AWG	15 ft. (4.6m) of 10/3 AWG	18 ft. (5.5m) power cord
NOZZLE	Choice of manual or automatic shutoff.	None	Choice of manual or automatic shutoff.
INLET/OUTLET SIZE	1 in. / 1 in.	1 in. / 1 in.	1 in. / 1 in.
SUCTION PIPE	None	None	None
HOSE	12 ft. (3.7m) x 1 in.	None	18 ft. (5.5m) x 1 in.
MOTOR PROTECTION	40 amp circuit breaker	40 amp circuit breaker	40 amp circuit breaker
UNIQUE FEATURE	Straight base, strainer screen without check valve.	Weight centering inlet base - includes check valve.	Weight centering inlet base - includes check valve.
USE WITH	Gasoline (up to 15% alcohol blends such as E15), diesel fuel (up to 20% biodiesel blends such as B20) and kerosene.		
APPROVALS	Motor is U.L. Listed to U.S. and Canadian Standards	Motor is U.L. Listed to U.S. and Canadian Standards	Motor is U.L. Listed to U.S. and Canadian Standards
WARRANTY	2 Year	2 Year	2 Year