




WHY GPI?

GPI OFFERS PRODUCT TRAINING, PLANOGRAM AND INVENTORY MANAGEMENT ASSISTANCE.

pump for your application. Contact GPI Customer Service for information on our Portable Cart (#142102-1) for these oil pumps * which can be found on page 37 of this catalog under "Accessories."

GPI PUMP SPECS	LIGHTWEIGHT AND EASY TO MOVE		
			
MODEL	L 5116*	L 5132*	PA-200-2UR
PART NUMBER	142100-01	142100-02	118003-11
VOLTAGE & TYPE	115/230 -volt AC - Aluminum Housing - Gerotor Gear	115/230 -volt AC - Aluminum Housing - Gerotor Gear	115-volt AC - Molded Plastic Housing - Gear
FLOWRATE	Up to 16 QPM (15 LPM)	Up to 32 QPM (30 LPM)	Up to 8 GPM (30 LPM)
DUTY CYCLE	30 min. On / 30 min. Off	30 min. On / 30 min. Off	30 min. On / 30 min. Off
POWER CORD	36 in. three-prong Grounded Plug	36 in. three-prong Grounded Plug	12 in. three-prong Power Connector
NOZZLE	3/4 in. Ball Valve Type	3/4 in. Ball Valve Type	1 in. Ball Valve Type
INLET/OUTLET SIZE	1 in. / 3/4 in.	1 in. / 3/4 in.	1 in. / 1 in.
SUCTION PIPE	Two-piece	Two-piece	Adjustable to 40 in.
HOSE	8 ft. (2.5m) x 3/4 in.	8 ft. (2.5m) x 3/4 in.	12 ft. (3.7m) x 1 in.
MOTOR PROTECTION	Thermally Protected	Thermally Protected	Thermally Protected
UNIQUE FEATURE	Lightweight and suitable for waste oil.	Lightweight and suitable for waste oil.	Built-in handle for portability and ease of use.
USE WITH	Oil (up to 90W), waste oil, hydraulic fluid, antifreeze and non-flammable oil-based solvents.	Oil (up to 90W), waste oil, hydraulic fluid, antifreeze and non-flammable oil-based solvents.	Petroleum based products, thin to medium lubricants and oil (up to 30W)
APPROVALS	Motor is U.L. Recognized Component and CSA Certified.	Motor is U.L. Recognized Component and CSA Certified.	CSA Certified
WARRANTY	1 Year	1 Year	2 Year