




# OIL PUMPS

## CHOOSING A GPI OIL PUMP

GPI Oil Pumps are specifically designed for use with high viscosity fluids. These weatherproof pumps will give you years of service. Consider the viscosity of the fluid being pumped and the temperature range when choosing the best oil

 <b>PUMP SPECS</b>				
	<b>MODEL</b>		<b>P-200-2UR</b>	
<b>PART NUMBER</b>	142100-03		118000-9	
<b>VOLTAGE &amp; TYPE</b>	12-volt DC Aluminum Housing - Gerotor Gear		12-volt DC Molded Plastic Housing - Gear	
<b>FLOWRATE</b>	Up to 16 QPM (15 LPM)		Up to 8 GPM (30 LPM)	
<b>DUTY CYCLE</b>	30 min. On / 30 min. Off		30 min. On / 30 min. Off	
<b>POWER CORD</b>	Minimum Gauge: 10/3 (not supplied) Do not exceed 15 ft. of cord.		15 ft. (4.6m) of 10/3 cord.	
<b>NOZZLE</b>	3/4 in. Ball Valve Nozzle		1 in. Ball Valve Nozzle	
<b>INLET/OUTLET SIZE</b>	1 in. / 3/4 in.		1 in. / 1 in.	
<b>SUCTION PIPE</b>	Two-piece		Adjustable to 40 in.	
<b>HOSE</b>	8 ft. (2.5m) x 3/4 in.		12 ft. (3.7m) x 1 in.	
<b>MOTOR PROTECTION</b>	Requires a 50 amp automotive-type fuse. (not supplied)		25 amp Inline Fuse (supplied)	
<b>UNIQUE FEATURE</b>	Lightweight and suitable for waste oil.		Built-in handle with convenient Spin Collar for easy installation.	
<b>USE WITH</b>	Oil (up to 90W), waste oil, hydraulic fluid, antifreeze and non-flammable oil-based solvents.		Thin to medium lubricants up to 30W oil. <b>Do not use with gasoline or diesel fuel.</b>	
<b>APPROVALS</b>	Motor is U.L. Recognized Component and CSA Certified.		CSA Certified	
<b>WARRANTY</b>	1 Year		2 Year	