

PETROLEUM CORO-VANE® PUMPS (TRUCK: DOUBLE SHAFT PT-SERIES) DECEMBER 1, 2013

Base model number	PT20	PT25	PT30
Base list price	\$1,563	\$1,792	\$2,251
Shipping weight (bare pump) lb. (kg)	68 (31)	87 (40)	139 (63)

Base model number (with hydraulic drive option)*	PTH20	PTH25	PTH30
Base list price	\$1,917	\$2,147	\$2,625
Shipping weight (bare pump) lb. (kg)	73 (33)	92 (42)	145 (66)

*Comes standard with SAE two bolt "A" with 1" keyed hydraulic motor shaft.

BASE X X X X X X X

SPECIFICATIONS

Strainer	No strainer	Standard	Standard	Standard	N
	Strainer	\$193	\$205	\$220	S

Internal bypass valve	Bypass valve	Standard	Standard	Standard	S
	Air operated valve	\$323	\$331	\$523	A

Bypass valve spring	35 – 50 psi	No charge	NA	NA	4
	50 – 75 psi	No charge	NA	NA	1
	75 – 110 psi	Standard	NA	NA	2
	110 – 125 psi	No charge	NA	NA	3
	50 – 110 psi	NA	Standard	Standard	2
	110 – 125 psi	NA	No charge	No charge	3

Seal O-ring material	Buna-N	\$109	\$109	\$109	A
	Viton®	Standard	Standard	Standard	D

Seal seat material	Cast iron	Standard	Standard	Standard	2
---------------------------	-----------	----------	----------	----------	---

Inlet flange	2 in NPT	Standard	No charge	NA	E
	2.5 in. NPT	NA	Standard	NA	J
	3 in. NPT	NA	NA	Standard	P
	2 in BSPT	\$42	\$48	NA	M
	2.5 in. BSPT	NA	\$48	NA	N
	3 in. BSPT	NA	NA	\$48	R
	2 in. Weld	\$86	NA	NA	F
	2.5 in. Weld	NA	\$103	NA	K
	3 in. Weld	NA	NA	\$103	Q
Less flange	-\$18	-\$18	-\$21	X	

Outlet flange	2 in. NPT	Standard	No charge	NA	E
	2.5 in. NPT	NA	Standard	NA	J
	3 in. NPT	NA	NA	Standard	P
	2 in BSPT	\$42	\$48	NA	M
	2.5 in. BSPT	NA	\$48	NA	N
	3 in. BSPT	NA	NA	\$48	R
	2 in. Weld	\$86	NA	NA	F
	2.5 in. Weld	NA	\$103	NA	K
	3 in. Weld	NA	NA	\$103	Q
Less flange	-\$18	-\$18	-\$21	X	

NA = Not available

All prices EXW (Ex Works) Oklahoma City • Refer to our sales policy for more details.