

Roper Pumps

5600

Series

FOR YOUR HIGH SOLID  
& HEAVY LIQUID  
TRANSFER DUTIES

## EXTREME SERVICE



### Applications

- Oil field service
- Brine and Raw water
- Sludges and slurry
- Waste oils, Tallow, etc.
- Sealant coats
- Molasses feeds
- Fertilizers
- Paper pulps

### Features

- Reversible rotation and flow
- Interchangeable parts with Bowie's 3300
- Easy maintenance
- External greasing
- Latest rubber technology
- 3" pump size  
Weight with flanges is approximately 142 lbs





Roper Pump Company

P.O. Box 269 • Commerce, GA 30529

Tele: 706-335-5551 • Fax: 706-335-5490

sales@roperpumps.com

Visit Us On The WorldWide Web

www.roperpumps.com

## 5600 Series

Pump Model	Theoretical Capacity	Maximum Speed	Maximum Flow at Maximum Speed	Maximum Temperature	Maximum Pressure	NPT Ports
5658	0.580 GPR	400 RPM	232.0 GPM (at 10 psi)	160°F	100 PSI (7 Bar)	3"

## Materials of Construction

Housing	Gears	Bearings	Shaft	Seal
Cast Iron	Nitrile Covered	Bronze	Steel	Packing

## Dimensional Chart and Diagram (Inches)

