

SOTERA™ SYSTEMS

SERIES 400B DIAPHRAGM PUMPS

MODELS AVAILABLE:
SS415BX731PG (12 Volt)
SS460BX731PG (115 Volt)

We combined many of the features of an air operated double diaphragm pump with the convenience and efficiency of an electromechanical drive design to create a compact, efficient product that will meet all your needs.

PUMP SPECS

- Reciprocating, Spring-Driven, Dual-Diaphragm Design
- Up to 15 GPM (1.5 CPS)
- Up to 9.5 GPM (350 CPS)
- Fluid Viscosities up to 3000+ CPS
- Particle Tolerance up to 0.1" diameter
- Floor Mount or 2" Bung Mount

FLUIDS HANDLED

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Motor Oil	•	•	•	•	•	•	•	•	•	•	•	•
Waste Oil	•	•	•	•	•	•	•	•	•	•	•	•
Hydraulic Fluid	•	•	•	•	•	•	•	•	•	•	•	•
Transmission Fluid	•	•	•	•	•	•	•	•	•	•	•	•
Soaps & Cleaning Fluids	•	•	•	•	•	•	•	•	•	•	•	•
Anti Freeze	•	•	•	•	•	•	•	•	•	•	•	•
Propionic Acid Hay				•	•	•	•	•	•	•	•	•
Seed Treatment Liquids	•	•	•						•	•	•	•
Crop Protection Materials		•	•	•	•	•	•	•	•	•	•	•
Fertilizers			•	•	•	•	•	•	•	•	•	•
Water	•	•	•	•	•	•	•	•	•	•	•	•

*Many other Applications



* Included but not shown is a telescoping Polypropylene suction tube, 12' outlet EPDM Ag hose, 3' EPDM inlet Ag hose, shut off ball valve, and all connection fittings.

MOTOR

- Available in 12 Volt or 115 Volt
- 1/4 - Horsepower
- Thermal Overload Protection



INLET / OUTLET PORTS

- 1" FNPT

MATERIALS

- Glass Filled Polypropylene Exterior
- Polypropylene, Santoprene EPDM, and Stainless Steel Wetted Internals

Includes all Hardware Required to Mount Directly to Drums & Totes

