



**WATER
BLUE MAMBA**
STANDARD DUTY DISCHARGE



FEATURES & APPLICATIONS:

- Designed for water discharge applications in agriculture, construction, industry. Strong, lightweight discharge hose. Rolls up flat for easy storage. The working pressure ratings are based on ambient temperature of 70° F & will vary inversely with temperature changes.

TECHNICAL DATA:

- **Temp Range:** -5° F to +130° F
- **Cover:** Blue PVC
- **Tube:** Blue PVC
- **Reinforcement:** 2 spiral plies
- **Safety Factor:** 3:1 min
- **Branding:**

BLUE PVC

ID	OD	Length	Working Pressure	Burst Pressure	Bend Radius	lbs per 100 ft.	Vacuum Rating "HG"	Part #
1"	---	300'	70	210	n/a	32	n/a	LD 100
1-1/4"	---	300'	70	210	n/a	38	n/a	LD 125
1-1/2"	---	300'	70	210	n/a	42	n/a	LD 150
2"	---	300'	65	195	n/a	60	n/a	LD 200
2-1/2"	---	300'	55	165	n/a	78	n/a	LD 250
3"	---	300'	55	165	n/a	90	n/a	LD 300
4"	---	300'	55	150	n/a	120	n/a	LD 400
5"	---	300'	50	120	n/a	171	n/a	LD 500
6"	---	300'	40	120	n/a	225	n/a	LD 600
8"	---	300'	40	120	n/a	330	n/a	LD 800
10"	---	100'	40	105	n/a	181	n/a	LD 1000
12"	---	100'	35	90	n/a	195	n/a	LD 1200



Information contained on this page is for general information purposes only. Seal Fast Inc. assumes no responsibility for errors or omissions for this product.