



VALVES

**SYRACO OIL & MOLASSES GATE
- CAST IRON**

FEATURES & APPLICATIONS:

- Excellent for dispensing heavy oils, light grease, molasses, honey, cream & other non-flammable viscous fluids
- Machined & lapped brass faceplate for smooth operation & perfect seal
- 45-60 degree discharge for optimum flow control
- Short, sturdy, two inch metal stamped handle provides easy flow control
- Brass faceplate designed for oval discharge to ensure no splashing
- Durable black enamel cast iron body

TECHNICAL DATA:

- **WOG** = Rating indicates the maximum non-shock pressure at ambient temperatures at which the valve may be used.
- **CWP** = Cold working pressure

WOG: Water, Oil & Gas: This was an older, generic pressure rating call-out which has been largely replaced by CWP. In this designation, "GAS" refers to any non-flammable, compressible fluid in a gaseous state. It does not imply a product's suitability or third-party approval for use with flammable gases. Similarly, in this designation, "Oil" does not imply a product's third-party approval for use with any petroleum products.



These faucets are intended for non-flammable viscous liquids stored in or dispensed from non-pressurized containers at ambient room temperature.

DISCLAIMER

All drawings and specifications are subject to change without notice. Drawings represent general dimensions of our products. Seal Fast Inc. cannot guarantee the dimensions will exactly match those in the drawing. The drawing is the property of Seal Fast Inc. Copying or reproduction of this drawing is expressly prohibited.

CAST IRON

Size	Part #
3/4"	71
1"	72
1-1/4"	73
1-1/2"	74
2"	75
3"	39
4"	40