


Hose I.D.	1/4" (6.4 mm)	3/8" (9.5 mm)	1/2" (12.7 mm)	3/4" (19.1 mm)	1" (25.4 mm)	
Hose O.D.	.530" (13 mm)	.710" (18 mm)	.850" (22 mm)	1.188" (30 mm)	1.380" (35.0 mm)	
"F" Width	Weight	Hose Capacity				
6" (152 mm)	38 lb (18 kg)	200' (61 m)	140' (43 m)	100' (30 m)	50' (15 m)	N/A
12" (305 mm)	46 lb (21 kg)	425' (130 m)	300' (91 m)	200' (61 m)	100' (30 m)	N/A
18" (457 mm)	54 lb (24 kg)	625' (191 m)	450' (137 m)	325' (99 m)	175' (54 m)	100' (31 m)
22" (559 mm)	58 lb (27 kg)	780' (238 m)	550' (168 m)	400' (122 m)	225' (69 m)	125' (38 m)
27" (686 mm)	66 lb (30 kg)	1000' (305 m)	700' (213 m)	500' (152 m)	275' (84 m)	150' (46 m)

Note: Weights listed are for crank driven. Add for power driven, electric - all explosion proof 45 lb. (20.41 kg); 12 V DC 1/3 HP 30 lb. (13.61 kg); Air 6 AM 36 lb. (16.33 kg). *Note: capacity chart is reference only.

Model Number Significance



Note: Many more reel models available in addition to chart. Please contact manufacturer for details.

Model without hose & bumper	Shipping Weight		Hose I.D.		Hose O.D.		Capacity		Pressure		(F)NPTF Reel Outlet	(F)NPTF Reel Inlet	D		E		F		
	lbs	kg	in	mm	in	mm	ft	m	psi	bar	in	in	in	mm	in	mm	in	mm	
Hand Crank Hose Reels Temperature operating range from -20 °F (-29 °C) to +250 °F (121 °C)																			
CA32106 L	40	18	1/2	13	.750	19	100	30	1000	69	1/2	1/2	93/4	248	193/4	502	6	152	
CA32112 L	46	21	1/2	13	.750	19	200	61	1000	69	1/2	1/2	153/4	400	253/4	654	12	305	
CA32118 L	51	23	1/2	13	.750	19	325	99	1000	69	1/2	1/2	213/4	552	313/4	806	18	457	
CA32122 L	65	29	1/2	13	.750	19	400	122	1000	69	1/2	1/2	253/4	654	353/4	908	22	559	
CA32128 L	69	31	1/2	13	.750	19	500	152	1000	69	1/2	1/2	303/4	781	403/4	1035	27	686	
CA32106 M	42	19	1/2	13	.850	22	100	30	3000	207	1/2	1/2	93/4	248	193/4	502	6	152	
CA32112 M	46	21	1/2	13	.850	22	200	61	3000	207	1/2	1/2	153/4	400	253/4	654	12	305	
CA32118 M	52	24	1/2	13	.850	22	325	99	3000	207	1/2	1/2	213/4	552	313/4	806	18	457	
CA33106 L	41	19	3/4	19	1.075	27	50	15	1000	69	3/4	3/4	93/4	248	193/4	502	6	152	
CA33112 L	46	21	3/4	19	1.075	27	100	30	1000	69	3/4	3/4	153/4	400	253/4	654	12	305	
CA33118 L	51	23	3/4	19	1.075	27	175	53	1000	69	3/4	3/4	213/4	552	313/4	806	18	457	
CA33112 M	47	21	3/4	19	1.188	30	100	30	3000	207	3/4	3/4	153/4	400	253/4	654	12	305	
CA33118 M	51	23	3/4	19	1.188	30	175	53	3000	207	3/4	3/4	213/4	552	313/4	806	18	457	
CH37118 L	54	24	1	25	1.375	35	100	30	300	21	1	1	213/4	552	313/4	806	18	457	
CH37122 L	61	28	1	25	1.375	35	125	38	300	21	1	1	253/4	654	353/4	908	22	559	
CH37128 L	65	29	1	25	1.375	35	150	46	300	21	1	1	303/4	781	403/4	1035	27	686	
Bevel Crank Hose Reels Temperature operating range from -20 °F (-29 °C) to +250 °F (121 °C)																			
BA36112 L	57	26	1/4	6	Twin Welding	250	76	200	14	1/4	1/4	153/4	400	253/4	654	12	305		
BA34112 M	54	24	1/2	13	Twin Hydraulic	100	30	3000	207	1/2	1/2	153/4	400	253/4	654	12	305		
Electric Motor Driven Hose Reels Temperature operating range from -20 °F (-29 °C) to +250 °F (121 °C)																			
EA32106 L10A	61	28	1/2	13	.750	19	100	30	1000	69	1/2	1/2	93/4	248	195/8	498	6	152	
EA32112 L12D	64	29	1/2	13	.750	19	200	61	1000	69	1/2	1/2	153/4	400	237/8	606	12	305	
EA32118 L12D	68	31	1/2	13	.750	19	325	99	1000	69	1/2	1/2	213/4	552	295/8	752	18	457	
EA33112 L12D	68	31	3/4	19	1.075	27	100	30	1000	69	3/4	3/4	153/4	400	237/8	606	12	305	
EA33118 L12D	68	31	3/4	19	1.075	27	175	53	1000	69	3/4	3/4	213/4	552	295/8	752	18	457	
EA33112 M12D	71	32	3/4	19	1.188	30	100	30	3000	207	3/4	3/4	153/4	400	237/8	606	12	305	
EA33128 M12D	91	41	3/4	19	1.188	30	275	84	3000	207	3/4	3/4	303/4	781	385/8	981	27	686	
EA33112 M24D	71	32	3/4	19	1.188	30	100	30	3000	207	3/4	3/4	153/4	400	237/8	606	12	305	
EH37118 L12D	71	32	1	25	1.375	35	100	30	300	21	1	1	213/4	552	31	787	18	457	
Air Motor Driven Hose Reels Filter, regulator, lubricator required. Temperature operating range from -20 °F (-29 °C) to +250 °F (121 °C)																			
AA32112 L4A	62	28	1/2	13	.750	19	200	61	1000	69	1/2	1/2	153/4	400	231/4	591	12	305	
AA33106 L4A	59	27	3/4	19	1.075	27	50	15	1000	69	3/4	3/4	93/4	248	171/4	438	6	152	
AA33112 L6A	68	31	3/4	19	1.075	27	100	30	1000	69	3/4	3/4	153/4	400	231/4	591	12	305	

All Series 30000 reels are supplied without hose. Assemblies quoted upon request. **CAUTION:** To prevent drum damage, fully extend and pressurize hose and rewind on the reel. For all metric thread connections over 1/2" add the suffix number 70 to indicate BSPT threads - example CA33112 M70.