

Power and Light Cord Reels | Series L4000 / L5000 / L7000

Made
in USA

Heavy duty
triple receptacle
L 4545 123 9G

NEW!



Heavy duty
flying lead
L 4050 163 X

Heavy duty GFCI
duplex outlet box
L 4545 123 7

- ✓ Compact for critical space requirements
- ✓ Durable abrasion and corrosion resistant baked-on powder coat finish
- ✓ Engineered for industrial use
- ✓ All models supplied with cord are complete with approximately 4-5 foot pigtail and three-prong plug
- ✓ Adjustable cord stop
- ✓ Wall, ceiling or bench mount

Model with Cord	Cord Ending	Cord Specifications				Volts	Amps	Shipping Weight		Size Index #
		AWG	mm	# Cond.	ft m			Type	lbs	
L 4035 163 3	Single Receptacle	16	1.33	3	35 11	SJTOW	125	13	25 11	1
L 4050 163 3	Single Receptacle	16	1.33	3	50 15	SJTOW	125	13	26 12	1
L 4545 123 3	Single Receptacle	12	3.32	3	45 14	SJEOOW	125	15	27 12	1
L 5550 123 3	Single Receptacle	12	3.32	3	50 15	SJEOOW	125	15	44 20	3
L 4545 123 3A	Single Receptacle	12	3.32	3	45 14	SJEOOW	125	20	28 13	1
L 5550 123 3A	Single Receptacle	12	3.32	3	50 15	SJEOOW	125	20	44 20	3
L 4545 123 3B	Twist Lock Connector	12	3.32	3	45 14	SJEOOW	125	20	28 13	1
L 5550 123 3B	Twist Lock Connector	12	3.32	3	50 15	SJEOOW	125	20	44 20	3
L 5750 103 4	R.V. Plug	10	5.37	3	50 15	SOOW	125	30	50 23	4
L 4545 123 7	Duplex Outlet Box w/GFCI (F)*	12	3.32	3	45 14	SJEOOW	125	15	29 13	1
L 4545 123 7A	Duplex Outlet Box w/GFCI (F)*	12	3.32	3	45 14	SJEOOW	125	20	29 13	1
L 4545 123 7B	Duplex Outlet Box	12	3.32	3	45 14	SJEOOW	125	20	29 13	1
L 5550 123 7	Duplex Outlet Box w/GFCI (F)*	12	3.32	3	50 15	SEOOW	125	15	45 20	3
L 4050 163 9	Triple Tap	16	1.33	3	50 15	SJEOOW	125	13	26 12	1
L 4545 123 9	Triple Tap	12	3.32	3	45 14	SJEOOW	125	15	28 13	1
L 4545 123 9G	Triple Tap w/GFCI(F)	12	3.32	3	45 14	SJEOOW	125	15	29 13	1

For indoor non-weather tight applications only. All models UL listed at 125 Volt 60 Hz single phase. *The GFCI Receptacle is designed to protect from line-to-ground shock hazards. The Ground Fault Circuit Interrupter does not protect against short circuits or overloads; this is the function of the fuse or circuit breaker. Reference page 6 for guide arm positions. **NOTE:** Swing brackets should be used if cords are pulled at more than 45°.

Cord Options

	#3 - Single Receptacle Single 15 AMP receptacle with clamp type strain relief available for both 16 AWG and 12 AWG cord. NEMA 5-15R
	#3A - Single Receptacle Single 20 AMP receptacle. NEMA 5-20R
	#3B - Twist Lock Connector Single 20 AMP receptacle with twist lock connector. NEMA L5-20R
	#4 - R.V. Plug Male rubber plug used with recreational vehicles (RV's).
	#7 / 7A / 7B - Duplex Outlet Box Duplex outlet box with flip-top lid. GFCI protection on #7 and 7A.
	#9 / 9G - Triple Tap NEW! Molded triple tap. GFCI protection on #9G only.
	X - Flying Lead Bare cord or cable endings and conduit box.

Flying Lead Model with Cord	Model No Cord	Cord Specifications				Volts/ Amps	Volts/ Amps	Shipping Weight*		Size Index #
		AWG	mm	# Cond.	ft m			Type	lbs	
L 4050 163 X	L 4000	16	1.33	3	50 15	SJEOOW	125 / 13	22 10	1	
-----	L 4100	16	1.33	4	40 12	SJEOOW	125 / 13	22 10	1	
L 4545 123 X	L 4500	12	3.32	3	45 14	SJEOOW	125 / 20	22 10	1	
-----	L 5000	10	5.27	3	35 11	SO	125 / 30	22 10	1	
-----	L 5400	12	3.32	3	35 11	SJEOOW	125 / 13	25 11	2	
L 5550 123 X	L 5500	12	3.32	3	50 15	SEOOW	125 / 20	35 16	3	
L 5550 124 X	-----	12	3.32	4	50 15	SEOOW	-----	600 / 16	44 20	3
L 5750 103 X	L 5700	10	5.27	3	50 15	SEOOW	125 / 30	220 / 15	37 17	4
-----	L 7000	16	1.33	4	35 11	SOOW	-----	220 / 45	41 19	**
L 7050 104 X	-----	10	5.27	4	50 15	SEOOW	-----	600 / 20	65 29	**

For indoor non-weather tight applications only. All models UL listed at 125 Volt 60 Hz single phase. *Weight of model without cord. **Refer to reelcraft.com.

Available
Options

Mounting
Brackets
See page 47



Replacement
Bumpers
See page 49

