

AUTOMATIC TANK GAUGES

SELECTING AN AUTOMATIC TANK GAUGE



Franklin Fueling Systems





SELECTING AN AUTOMATIC TANK GAUGE

When you fully understand both your current site needs and where you might be headed in the future, you are able to make a sound ATG selection. Be sure to address your compliance needs and operational requirements when considering which ATG is right for you. The EVO™ Series offers you four different options with right-sized features to meet the requirements of your specific application, size, and compliance needs.

Which ATG is right for your application?

| | | | | |
|---|--------------|--------------|---------------------|---------------------|
| Maximum tank capacity | 6 | 14 | 36* | 36* |
| Maximum sensor input capacity | 6 | 14 | 48* | 96* |
| Total # of inputs | 6 | 14 | 48 | 96 |
| Line capacity | - | - | 24 | 24 |
| Dry contact input channels | 2 | 2 | 2 | 2 |
| AC input channels | - | - | 36 | 36 |
| 4-20 ma input channels | - | - | 24 | 24 |
| Relay output channels | 2 | 2 | 26 | 50 |
| Display type | 7" Color LCD | 7" Color LCD | 7" Color LCD | 7" Color LCD |
| Printer options | External | External | Internal & External | Internal & External |
| Internal audible alarm | ✓ | ✓ | ✓ | ✓ |
| Email/SMS notifications | ✓ | ✓ | ✓ | ✓ |
| Inventory and delivery management | ✓ | ✓ | ✓ | ✓ |
| Leak detection sensors | ✓ | ✓ | ✓ | ✓ |
| Static and Continuous tank testing | ✓ | ✓ | ✓ | ✓ |
| Static and Statistical Electronic Line Leak Detection | | | ✓ | ✓ |
| High/low product, water, and temperature alarm set points | ✓ | ✓ | ✓ | ✓ |
| Inventory reconciliation / tank autocalibration | ✓ | ✓ | ✓ | ✓ |
| Density and mass measurement | ✓ | ✓ | ✓ | ✓ |
| Phase separation detection | ✓ | ✓ | ✓ | ✓ |
| Secondary Containment Monitoring (vacuum) | | | ✓ | ✓ |
| Turbine Pump Interface | ✓ | ✓ | ✓ | ✓ |
| DEF/AdBlue® recirculation system | | | ✓ | ✓ |
| Back-up generator monitoring | ✓ | ✓ | ✓ | ✓ |
| Fuel flow control | | | ✓ | ✓ |
| MODBUS® compatibility | | | ✓ | ✓ |



EVO™ 200



EVO™ 400



EVO™ 550



EVO™ 5000

*Additional capacity available with expansion console.



Franklin Fueling Systems

franklinfueling.com
3760 Marsh Rd. • Madison, WI 53718, USA
Tel: +1 608 838 8786 • Fax: +1 608 838 6433
Tel: USA & Canada +1 800 225 9787 • Tel: UK +44 (0) 1473 243300
Tel: Mex 001 800 738 7610 • Tel: FR +33 (0) 1 69 21 41 41 • Tel: CH +86 10 8565 4566



© 2017 Franklin Fueling Systems. All Rights Reserved.

FFS-0621 08-17