

# DEF/UTILITY PUMPS

## TECHNICAL DATA SHEET



LEGACY OF RETAIL  
FUEL TRANSFER SOLUTIONS

The GPI DEF / Utility Pumps are available in two power supply options: 115V (AC) for stationary applications and 12V (DC) for mobile applications.

### D08TS-115PO

**115V AC**

Voltage (Power Source)



### WETTED MATERIALS (ALL MODELS)

Pump Housing:	Nylon
Diaphragm:	TPU
Seals:	EPDM
Motor Shaft & Fasteners:	Stainless Steel

### SPECS (ALL MODELS)

Max. Flow Rate:		8 GPM   30 L/min
Max. Discharge Pressure:		Up to 23 PSI (1.6 bar)
At Sea Level 70° F (21.1° C)	Suction Lift:	Up to 9 ft. (2.75 m)
	Discharge Lift:	Up to 15 ft. (4.5 m)
Warranty:		Two-Year Pump and Meter

### D08TS-012PO

**12V DC**

Voltage (Power Source)



### FLUIDS

For use with Diesel Exhaust Fluid (DEF), Antifreeze, Windshield Wash Fluid, Ammonium Sulfate, Non-Potable Water, and other water-based chemicals. See wetted materials list.  
**Not compatible with petroleum-based liquids. DO NOT USE WITH FLAMMABLE LIQUIDS.**

### DEF SYSTEM MODEL NUMBERS

**Example:**  
D08TS-115PO

Example:

D08TS-115PO

D	08	TS	-	115	PO
Type	Flow Rate	Wetted Materials	-	Power	Suffix

Pump Type

D	Diaphragm
---	-----------

Flow Rate

08	GPM
----	-----

Wetted Materials

T	TPU
S	Stainless Steel

Voltage

012	V (DC)
115	V (AC)

Option

DA	DEF Automatic Nozzle
PO	Pump Only

GREAT PLAINS INDUSTRIES



## SPECS (ALL MODELS)

Type:	Oscillating Diaphragm
Motor RPMs:	1750
Duty Cycle:	20 min.

Operating Temperature:	23° F to 104° F (-5° C to 40° C)
Inlet:	¾ in. Hose Barb
Outlet:	¾ in. Hose Barb



## DIMENSIONS

## D08TS-115PO

Part No.:	180000-01
Motor HP:	0.50
Voltage, Input:	115V (AC) 50/60 Hz
Amps (Rated):	1.3
Motor Protection:	Resetting Thermal Protector
Power Cord:	4.5 ft. (1.4 m), 18AWGx3C, Factory-Installed
What's in the Box:	115-Volt DEF Transfer Pump, Hose barb inlet and outlet fittings, Hose clamps

Refer to product owner's manual for installation and safety instructions.



## DIMENSIONS

## D08TS-012PO

Part No.:	180002-01
Motor HP:	0.24
Voltage, Input:	12V (DC)
Amps (Rated):	14.8
Motor Protection:	15 Minute Timer Circuit
Power Cord:	4.5 ft. (1.4 m), 14AWGx2C, Factory-Installed
What's in the Box:	12-Volt DEF Transfer Pump, Hose barb inlet and outlet fittings, Hose clamps

Refer to product owner's manual for installation and safety instructions.