602 & 602DEF Series Automatic Shut-Off Nozzles

Application

Husky brand automatic shut-off nozzles are designed for dispensing motor fuel in retail and commercial applications. Nozzle automatically shuts off when the tank is full.

Features and Details

- **602**...high volume truck nozzle with a three-notch hold-open clip and full grip guard
- **602GS**...general service nozzle with a three-notch hold-open clip, full grip guard, and hanging hook
- **602X**...conventional fueling nozzle with a three-notch hold-open clip and full grip guard
- **602XS**...pressure activated conventional fueling nozzle with a threenotch hold-open clip and full grip guard
- **602HVS**...high volume pressure activated nozzle with a black hand guard, spout bushing, hold-open clip, full grip guard, and waffle splash guard

Materials of Construction

- Aluminum body
- UL listed

Item Number	Size	Spout Size	Weight (lbs)
6020700 1N	1″	15/16″	3.0
602GS-0100 1N	1″	¹⁵ /16″	3.0
602GS-0200 1N	1″	¹³ /16″	3.0
602HVS0100 1N	1″	^{15/16} ″	3.0
602X0100 1N	3⁄4″	¹⁵ /16″	3.0
602X0200 1N	3⁄4″	¹³ /16″	3.0
602XS-0100 1N	3/4"	¹⁵ /16″	3.0
602XS-0200 1N	3/4"	¹³ /16″	3.0



Application

Automatic shut-off nozzles are designed for dispensing retail and commercial Diesel Exhaust Fluid (DEF). The nozzle automatically shuts off when the tank is full. Not compatible with Gilbarco DEF Dispenser Series.

Features and Details

 Optional Miss-filling Prevention Device (MFPD) is permanently installed in DEF tank fill pipe. Eliminates the risk of accidental DEF filling or

environmental contamination

Maximum flow rate is 11 GPM

MORRISON BROS. CO.

Materials of Construction

Stainless steel body

Item Number	Size	Miss-filling Device	Weight (Ibs)
602DEF0000 1N	¾″ NPT	No	5.20
602DEFM000 1N	¾″ NPT	Yes	5.30
602DEFB0000 1N	¾″ BSP	No	5.20
602DEFBM000 1N	¾" BSP	Yes	5.30
449SDM0500 1P		Yes	.50



570 E. 7th Street, P.O. Box 238 | Dubuque, IA 52004-0238 t. 563.583.5701 | 800.553.4840 | f. 563.583.5028 www.morbros.com

SPECIFICATION SHEET