





METERS



METERED NOZZLES





NOZZLES FILTRATION

P3.5:1

FEATURES

- DOUBLE EFFECT
- · LOW OPERATIONAL SPEED
- DURABILITY
- MAINTENANCE FREE
- 20% MORE POWERFUL COMPARED TO THE MARKET STANDARD
- COMPOSITE MATERIAL BODY
- NO OXIDATION/PARTICLES PROOF
- METAL FREE DIFFUSER

The Piusi P3.5:1 is an oil piston pump, suitable for transferring medium viscosity oil over short distances. It is manufactured using selected materials to ensure high performance and durability.

PIUSI 3.5 ST





PIUSI 3.5 940

PERFORMANCE

up to
5.7 GPM

(up to 21.5 l/min)
FLOW RATE

43.5-116 BAR

AIR PRESSURE

MID-HIGH

VISCOSITY

BELOW
77 DB

NIOSE LEVEL**



	WEI	GHT	PACKAGING							
PART #	KG	LBS	ММ	INCH	PCS/PALLET	PCS/BOX				
PIUSI 3.5 ST										
F00214N00	3.5	7.7	495X125X13O	19.5X4.9X5.1	-	1				
PIUSI 3.5 940										
F00214N20	5.5	12.1	1250X125X13O	43.2X4.9X5.1	-	1				


































IN THE BOX

- BUNG ADAPTER
- PIUSI P3.5 ST / 940
- · INSTRUCTION MANUAL

DETAILS







DIMENSIONS

PIUSI P3	3.5 ST
MEASURE "A"	17.5"
MEASURE "B"	7"
WEIGHT	10 LB

PIUSI P3.5 940

MEASURE "A"	48"
MEASURE "B"	37"
WEIGHT	12 LB







MATERIALS

- AIR MOTOR: TECHNOPOLYMER
- BODY: DIE CAST STEEL
- SEAL: NBR

TECHNIC	TECHNICAL DATA															
PART #	DESCRIPTION	FLUIDS TYPE	FLOW RATE		COMPRESSION	WORKING PRESSURE		AIR CONSUMPTION	SUCTION PIPE		SUCTION PIPE		INLET	OIL SIDE CONNECTION		POLYURETHANE SEALS
			L/MIN	GPM	RATIO	BAR	PSI	GPM	IN	LENGTH IN	NPT	SUCTION NPT	OUTLET NPT	NPT		
PIUSI 3.5 ST																
F00214N00	3.5:1 STUB AIR-O- PERATED PISTON PUMP NPT	0	21.5	5.7	3.5:1	3-8	43.5-116	53-66	2"	6.7"	F.1/4"	F.1"	M.1/2"	YES		
PIUSI 3.5 94	10															
F00214N20	3.5:1 940 AIR-O- PERATED PISTON PUMP NPT	0	21.5	5.7	3.5:1	3-8	43.5-116	53-66	2"	37"	F.1/4"	F.1"	M.1/2"	YES		

*MEASURING MADE WITH PUMP ASSEMBLED OVER DRUM TAKEN FROM 3 FT DISTANCE WITHOUT ANY ENVIROMENTAL NOISES.

P3.5:1