





METERS



METERED NOZZLES





NOZZLES

VISCO-FLOWMAT

FEATURES

- ON DEMAND FLOW
- ELECTRONIC PRESSURE SWITCH
- BUILT-IN SECURITY VALVE
- HIGH PRESSURE

The Piusi VISCO-FLOWMAT is an electric gear pump suitable for transferring high viscosity oils. This self-priming pump is equipped with a pressure switch that features an automatic pump switch-off at the end of the delivery.

PERFORMANCE

up to
2000

cSt VISCOSITY

BELOW
70 DB

NOISE LEVEL**

up to
2.4 GPM

FLOW RATE

up to 363 PSI

PRESSURE





VISCO-FLOWMAT



PACKAGING									
PART #	WE	GHT	PACKAGING						
	KG	LBS	ММ	INCH	PCS/PALLET	PCS/BOX			
F0030201D	12	26.5	360X360X300	14.2X14.2X11.8	-	1			
F0030210D	15	33.1	360X360X300	14.2X14.2X11.8	-	1			































VISCO FLOWMAT 5.2 VISCO FLOWMAT 5.2 VISCO FLOWMAT 200/2 VISCO FLOWMAT 350/2

P = TOTAL PRESSURE (PSI)

IN THE BOX

- KIT PRIMING DEVICE
- KIT FLOWMAT
- VISCOMAT GEAR PUMP
- INSTRUCTION MANUAL

DETAILS






ADJUSTABLE BYPASS



TYPE OF FLUID OIL SAE 10W40

TEMPERATURE 20 °C





MATERIALS

- BODY: CAST IRON
- GEARS: SINTERED STEEL
- SHAFT: STEEL
- BYPASS: BRASS

TECHNICAL DATA												
D. D	DESCRIPTION	FLUIDS TYPE	FLOW RATE		WORKING PRESSURE		VOLTAGE		DD\4	INLET	BYPASS	
PART #			L/MIN	GPM	BAR	PSI	MOTOR V./ HZ	POWER WATT	AMP. MAX.	RPM	OUTLET NPT	VALVE
F0030201D	VISCOMAT 200/2 M+FLOWMAT-170 PSI 120/60	0	9	2.4	12	170	230/50/60	800	3,8	1450	I" NPT	YES
F0030210D	VISCOMAT 350/2 M+FLOWMAT-355PSI - 120/60	0	9	2.4	25	355	230/50	1250	6	1450	1" NPT	YES

UPON REQUEST IT IS AVAILABLE WITH DIFFERENT VOLTAGE AND FREQUENCY

VISCO-FLOWMAT