



SAYLOR-BEALL

AIR COMPRESSORS

ST. JOHNS,
980-224-2371

MICHIGAN
800-248-9001

SPLASH LUBRICATED AIR COMPRESSORS



451520



VT-735-80



AMERICAN MADE QUALITY



Distributed by: Westech Equipment
195 W. 3900 S. Salt Lake City, UT. 84107
1(800) 433-8831 westechequipment.com

SAYLOR-BEALL

**AIR
COMPRESSORS**

ST. JOHNS MICHIGAN
800.433.8831

WHAT MAKES A SAYLOR-BEALL?



Saylor-Beall uses piston rings specifically designed for two-stage air compressors. They have a special taper and an overlapping joint to eliminate ring gap. This ensures less compressed air blow-by and reduces oil carry-over.

HORIZONTAL TANK MOUNTED AIR COMPRESSORS

92024



735-80



Motor Horse Power	Tank Cap. (Gal)	Splash Lubricated Model	Splash Lubricated Pump	100 PSI Rating			175 PSI Rating			Dimensions LxWxH (inches)	Bolt Down L x W (inches)	Approx. Shipping Wt. (lbs)
				RPM	CFM Displ.	CFM Delvd.	RPM	CFM Displ.	CFM Delvd.			
1½	60 80	715-60 715-80	703	475	9.2	7.3	400	7.8	5.8	48x21x47 63x21x47	28x19 40x19	524 569
2	60 80	720-60 720-80	703	540	10.5	8.3	510	10.0	7.5	48x21x47 63x21x47	28x19 40x19	545 590
3	60 80 120	730-60 730-80 730-120	705	575	15.5	12.3	540	14.8	11.1	48x21x47 63x21x47 69x24x51	28x19 40x19 40x19	567 612 738
5	60 80 120	735-60 735-80 735-120	705	850	23.0	18.3	845	23.0	17.3	48x21x47 63x21x47 69x24x51	28x19 40x19 40x19	583 628 754
	80 120	737-80 737-120	707	515	27.9	22.2	455	24.7	18.5	63x21x47 69x24x51	40x19 40x19	717 845
7½	80 120	745-80 745-120	707	730	39.4	31.2	655	35.4	26.9	63x21x47 69x24x51	40x19 40x19	729 855
10	80 120	755-80 755-120	707	850	46.0	36.6	850	46.0	34.4	63x21x47 69x24x51	40x19 40x19	749 875
	120 200	451012 451020	4500	665	51.0	41.8	605	46.4	38.0	75x29x58 78x30x63	40x19 40x19	1161 1400
15	120 200	451512 451520	4500	830	63.7	52.2	830	63.7	51.0	75x29x58 78x30x63	40x19 40x19	1195 1434
	120 200	91512 91520	9000	550	84.4	72.1	480	73.7	61.2	75x29x58 78x30x63	40x19 40x19	1359 1601
20	120 200 240	92012 92020 92024	9000	665	102.1	86.1	605	92.8	76.1	75x29x58 78x30x63 85x30x63	40x19 40x19 51x22½	1404 1643 1858
25	120 200 240	92512 92520 92524	9000	780	119.7	101.6	710	109.0	89.6	75x29x58 78x30x63 85x30x63	40x19 40x19 51x22½	1418 1657 1872
30	120 200 240	93012 93020 93024	9000	830	127.4	104.5	830	127.4	101.1	75x29x58 78x30x63 85x30x63	40x19 40x19 51x22½	1439 1678 1893



SAYLOR-BEALL

AIR COMPRESSORS

S.T. JOHNS, MICHIGAN
989-224-2371 800-248-9001



VT-755-120



100% machined, assembled, and tested for quality in our plant in St. Johns, Michigan. We take pride in manufacturing an American made product.

VERTICAL TANK MOUNTED AIR COMPRESSORS

Motor Horse Power	Tank Cap. (Gal)	Splash Lubricated Model	Splash Lubricated Pump	100 PSI Rating			175 PSI Rating			Dimensions LxWxH (inches)	Bolt Down LxW (inches)	Approx. Shipping Wt. (lbs)
				RPM	CFM Displ.	CFM Delvd.	RPM	CFM Displ.	CFM Delvd.			
1½	60	VT-715-80	703	475	9.2	7.3	400	7.8	5.8	34x26x74	23x23	522
	80	VT-715-80								34x29x74	25½x25½	589
2	60	VT-720-80	703	540	10.5	8.3	510	10.0	7.5	34x26x74	23x23	543
	80	VT-720-80								34x29x74	25½x25½	610
3	60	VT-730-80	705	575	15.5	12.3	540	14.8	11.1	34x26x74	23x23	565
	80	VT-730-80								34x29x74	25½x25½	632
	120	VT-730-120								34x30x77	25½x25½	784
5	60	VT-735-80	705	850	23.0	18.3	845	23.0	17.3	34x26x74	23x23	581
	80	VT-735-80								34x29x74	25½x25½	648
	120	VT-735-120								34x30x77	25½x25½	800
	120	VT-737-120	707	515	27.9	22.2	455	24.7	18.5	44x30x75	25½x25½	905
7½	120	VT-745-120	707	730	39.4	31.2	655	35.4	26.9	44x30x75	25½x25½	915
10	120	VT-755-120	707	850	46.0	36.6	850	46.0	34.4	44x30x75	25½x25½	935

SAYLOR-BEALL Manufacturing Company warrants its compressors and parts when properly installed, lubricated and maintained as recommended and in accordance with good industry practice to be free from defects in material and workmanship under normal use and service. The responsibility of the Company under this warranty is limited to repair or replacement at the Company's factory, any compressor or part thereof, which shall, within one year after date of shipment to the original purchaser, be returned to the Company and which, upon examination, shall be found defective to the satisfaction of the Company. This warranty shall not apply to compressors or parts which have been subjected to misapplication, misuse, negligence or accident, to compressors or parts which have been repaired or tampered with outside the Company's factory when in the judgement of the Company, it appears that the reliability or stability of the compressor or part has been effected. Ordinary maintenance, such as adjustment and cleaning of equipment or components is the responsibility of the owner. All transportation and shipping charges shall be paid by purchaser. This warranty does not apply to electric motors or gasoline engines. These are covered by the Original Manufacturer's Warranty and should be returned by the purchaser to their authorized station for service. This warranty is expressly in lieu of all other warranties (except of title) expressed or implied and of any other obligations or liability on the part of the Company. There are no warranties of merchantability or of fitness for a particular purpose.